

ARTICLE 12: FLOODPLAIN STANDARDS

STATEMENT OF PURPOSE AND INTENT

Certain areas of the Town of Long Island, Maine are subject to periodic flooding, causing serious damages to properties within these areas. Relief is available in the form of Federally subsidized flood insurance as authorized by the National Flood Insurance Act of 1968.

Therefore, the Town of Long Island, Maine has chosen to become a participating community in the National Flood Insurance Program, and agrees to comply with the requirements of the National Flood Insurance Act of 1968 (P.L. 90-488, as amended) as delineated in the attached Floodplain Management Ordinance.

It is the intent of the Town of Long Island, Maine to require the recognition and evaluation of flood hazards in all official actions relating to land use in the floodplain areas having special flood hazards.

This body has the legal authority to adopt land use and control measures to reduce future flood losses pursuant to MRSA Title 30A, Sections 3001-3007, 4352 and 4401-4407.

SECTION I-ESTABLISHMENT

The Town of Long Island, Maine elects to comply with the requirements of the National Flood Insurance Act of 1968 (P.L. 90-488, as amended) . The National Flood Insurance Program, established in the aforesaid Act, provides that areas of the Town of Long Island having a special flood hazard be identified by the Federal Emergency Management Agency and that floodplain management measures be applied in such flood hazard areas. This Ordinance establishes a Flood Hazard Development Permit system and review procedure for development activities in the designated flood hazard areas of the Town of Long Island, Maine.

The areas of special flood hazard, Zones A, A1-30, AE, AO, AH, V1—30, and/or VE, identified by the Federal Emergency Management Agency in a report entitled “Flood Insurance Study-City of Portland, Maine, Cumberland County,” dated July 17, 1986 with accompanying “Flood Insurance Rate Map” dated July 15, 1992 and “Flood Boundary and Floodway Map,” dated July 17, 1986 is hereby adopted by reference and declared to be a part of this Ordinance.

SECTION II-PERMIT REQUIRED

Before any construction or other development (as defined in Section XIII), including the placement of manufactured homes, begins within any areas of special flood hazard established in Section I, a Flood Hazard Development Permit shall be obtained from the Code Enforcement Officer. This permit shall be in addition to any other building permits which may be required pursuant to the codes and ordinances of the Town of Long Island, Maine.

SECTION III-APPLICATION FOR PERMIT

The application for a Flood Hazard Development Permit shall be submitted to the Code Enforcement Officer and shall include:

- A. The name and address of the applicant;
- B. An address and a map indicating the location of the construction site;
- C. A site plan showing location of existing and/or proposed structures, sewage disposal facilities, water supply facilities, areas to be cut and filled, and lot dimensions;
- D. A statement of the intended use of the structure;
- E. A statement as to the type of sewage system proposed;
- F. Specification of dimensions of the proposed structure;
- G. The elevation in relation to the National Geodetic Vertical Datum (VGVD) or to a locally established datum in Zone A only, of the:
 - 1. base flood at the proposed site of all new or substantially improved structures, which is determined:
 - a. in Zones A1-30, AE, AO, AH, V1-30, and VE from data contained in the “Flood Insurance Study -Town of Long Island, Maine,” as described in Section I; or,
 - b. in Zone A, to be the elevation of the ground at the intersection of the floodplain boundary and a line perpendicular to the shoreline which passes along the ground through the site of the proposed building;
 - 2. highest and lowest grades at the site adjacent to the walls of the proposed building;
 - 3. lowest floor, including basement; and whether or not such structures contain a basement; and,
 - 4. level, in the case of non-residential structures only, to which the structure will be floodproofed;
- H. A description of a base flood elevation reference point established on the site of all new or substantially improved structures;
- I. A written certification by a registered land surveyor that the elevations shown on the application are accurate;
- J. Certification by a registered professional engineer or architect that floodproofing methods for any:
 - 1. non-residential structures will meet the floodproofing criteria of Section III.G.4; Section VI.G; and other applicable standards in Section VI; and,
 - 2. construction in coastal high hazard areas, Zones V1-30 and VE, will meet the floodproofing criteria of Section VI.K; and other applicable standards in Section VI.
- K. A description of the extent to which any water course will be altered or relocated as a result of the proposed development; and
- L. A statement of construction plans describing in detail how each applicable development standard in Section VI will be met.

SECTION IV-APPLICATION FEE AND EXPERT'S FEE

A non—refundable application fee of \$50.00 shall be paid to the Town Clerk and a copy of a receipt for the same shall accompany the application.

An additional fee may be charged if the Code Enforcement Officer and/or Board of Appeals needs the assistance of a professional engineer or other expert. The expert's fee will be paid in full by the applicant within 10 days after the town submits a bill to the applicant. Failure to pay the bill shall constitute a violation of the ordinance and be grounds for the issuance of a stop work order. An expert shall not be hired by the municipality at the expense of an applicant until the applicant has either consented to such hiring in writing or been given an opportunity to be heard on the subject. An applicant who is dissatisfied with a decision of the Code Enforcement Officer may appeal that decision to the Board of Appeals.

SECTION V - REVIEW OF FLOOD HAZARD DEVELOPMENT PERMIT APPLICATIONS

The Planning Board shall:

- A. Review all applications for the Flood Hazard Development Permit to assure that proposed building sites are reasonably safe from flooding and to determine that all pertinent requirements of Section VI (Development Standards) have, or will be met;
- B. Utilize, in the review of all Flood Hazard Development Permit applications, the base flood data contained in the "Flood Insurance Study-Town of Long Island, Maine," as described in Section I. In special flood hazard areas where base flood elevation data are not provided, the Code Enforcement Officer shall obtain, review and reasonably utilize any base flood elevation and floodway data from federal, state, or other sources, including information obtained pursuant to Section III.G.1.b.; Section VI.I; and Section VIII.D, in order to administer Section VI of this Ordinance;
- C. Make interpretations of the location of boundaries of flood hazard areas shown on the maps described in Section I of this Ordinance;
- D. In the review of Flood Hazard Development Permit applications, determine that all necessary permits have been obtained from those federal, state and local government agencies from which prior approval is required by federal or state law, including but not limited to Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334;
- E. Notify adjacent municipalities, the Department of Environmental Protection, and the Maine Office of Community Development prior to any alteration or relocation of a water course and submit copies of such notification to the Federal Emergency Management Agency;
- F. Issue a two part Flood Hazard Development Permit for elevated structures. Part I shall authorize the applicant to build as structure to and including the first horizontal floor only above the base flood level. At that time the applicant shall provide the Code Enforcement Officer with an application for Part II of the Flood Hazard Development Permit and shall include an Elevation Certificate completed by a registered Maine surveyor for compliance with the elevation requirements of Section VI, paragraphs F, G, H, and K. Following review of the application, which review shall take place within 72 hours of receipt of the application, the Code Enforcement Officer shall issue Part II of the Flood Hazard Development Permit. Part II shall authorize the applicant to complete the construction project; and,

- G. Maintain, as a permanent record, copies of all Flood Hazard Development Permits issued and data relevant thereto, including reports of the Board of Appeals on variances granted under the provisions of Section IX of this Ordinance, and copies of Elevation Certificates and Certificates of Compliance required under the provisions of Section VII of this Ordinance.

SECTION VI.-DEVELOPMENT STANDARDS

All developments in areas of special flood hazard shall meet the following applicable standards:

- A. New construction or substantial improvement of any structure shall:
 - 1. be designed or modified and adequately anchored to prevent flotation, collapse or lateral movement of the structure resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy;
 - 2. use construction materials that are resistant to flood damage;
 - 3. use construction methods and practices that will minimize flood damage; and
 - 4. use electrical, heating, ventilation, plumbing, and air conditioning equipment, and other service facilities that are designed and/or located so as to prevent water during from entering or accumulating within the components during flooding conditions.
- B. All new and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the systems.
- C. All new and replacement sanitary sewage systems shall be designed and located to minimize or eliminate infiltration of flood waters into the system and discharges from the system into flood waters.
- D. On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during floods.
- E. All development shall be constructed and maintained in such a manner that no reduction occurs in the flood carrying capacity of any watercourse.
- F. New construction or substantial improvement of any residential structure located within:
 - 1. Zones A1-30, AE, and AH shall have the lowest floor (including basement) elevated to at least one foot above the base flood elevation.
 - 2. Zones AO and AH shall have adequate drainage paths around structures on slopes, to guide floodwater away from the proposed structures.
 - 3. Zone AO shall have the lowest floor (including basement) elevated above the highest adjacent grade:
 - a. at least one foot higher than the depth specified in feet on the community's Flood Insurance Rate Map; or,
 - b. at least three feet if no depth number is specified.
 - 4. Zone A shall have the lowest floor (including basement) elevated to at least one foot above the base flood elevation utilizing information obtained pursuant to Section III.G.1.b.; Section V.B; or Section VIII.D.
 - 5. Zones VI-30 and VE shall meet the requirements of Section VI.K.
- G. New construction or substantial improvement of any non-residential structure located within:

1. Zones A1-30, AE, and AH shall have the lowest floor (including basement) elevated to at least one foot above the base flood elevation, or together with attendant utility and sanitary facilities, shall:
 - a. be floodproofed to at least one foot above the base flood level so that below that elevation the structure is watertight with walls substantially impermeable to passage of water;
 - b. have structural components capable of resisting hydrostatic and hydrodynamic loads and the effects of buoyancy; and;
 - c. be certified by a professional engineer, or architect that the design and methods of construction are in accordance with accepted standards of practice for meeting the provisions of this section. Such certification shall be provided with the application for a Flood Hazard Development Permit, as required by Section III.J and shall include a record of the elevation above mean sea level of the lowest floor including basement.

 2. Zones AO and A1-f shall have adequate drainage paths around structures on slopes, to guide floodwater away from the proposed structures.

 3. Zone AO shall have the lowest floor (including basement) elevated above the highest adjacent grade:
 - a. at least one foot higher than the depth specified in feet on the community's Flood Insurance Rate Map; or,
 - b. at least three feet if no depth number is specified ; or,
 - c. together with attendant utility and sanitary facilities be floodproofed to meet the elevation requirements of this section and floodproofing standards of Section VI, paragraph G.1.

 4. Zone A shall have the lowest floor (including basement) elevated to at least one foot above the base flood elevation utilizing information obtained pursuant to Section III.G.1.b.; Section V.B; or Section VIII.D.

 5. Zones VI-30 and VE shall meet the requirements of Section VI.K.
- H. New or substantially improved manufactured homes located within:
1. Zones A1-30, AE, or AH shall:
 - a. be elevated on a permanent foundation such that the lowest floor is at least one foot above the base flood elevation; and,
 - b. be securely anchored to an adequately anchored foundation system to resist flotation or lateral movement. Methods of anchoring may include, but are not limited to:
 - (1) over-the-top ties anchored to the round at the four corners of the manufactured home, plus two additional ties per side at intermediate points (manufactured homes less than 50 feet long require one additional tie
 - (2) frame ties at each corner of the home, plus five additional ties along each side at intermediate points (manufactured homes less than 50 feet long require four additional ties per side)

- (3) All components of the anchoring system described in Section VI, paragraph H.1.b (1) (2) shall be capable of carrying a force of 4800 pounds.
2. Zones A0 and AH shall have adequate drainage paths around structures on slopes, to guide floodwater away from the proposed structures.
3. Zone A0 shall have the lowest floor (including basement) elevated above the highest adjacent grade:
 - a. at least one foot higher than the depth specified in feet on the community's Flood Insurance Rate Map, or,
 - b. at least three feet if no depth number is specified; and,
 - c. meet the requirements of Section VI.H.1. (a) (b).
4. Zone A shall have the lowest floor (including basement) elevated to at least one foot above the base flood elevation utilizing information obtained pursuant to Section III.G.1.b ; Section V.6; or Section VIII.D.
5. Zones VI-30 and VE shall meet the requirements of Section VI.K.

I. Floodways

1. In Zones AI-30 and AE encroachments, including fill, new construction, substantial improvement, and other development shall not be permitted in riverine areas, for which a regulatory floodway is designated on the community's "Flood Boundary and Floodway Map, unless a technical evaluation certified by a registered professional engineer is provided demonstrating that such encroachments will not result in any increase in flood levels within the community during the occurrence of the base flood discharge.
 2. In Zones AI-30 and AE riverine areas, for which no regulatory floodway is designated, encroachments, including fill, new construction, substantial improvement, and other development shall not be permitted unless a technical evaluation certified by a registered professional engineer is provide demonstrating that the cumulative effect of the proposed development, when combined with all other existing development and anticipated development:
 - a. will not increase the water surface elevation of the base flood more than one foot at any point within the community; and,
 - b. is consistent with the technical criteria contained in Section 2-7 entitled "Hydraulic Analyses, Flood Insurance Study — Guidelines and Specifications for Study Contractors, FEMA 37/September,1985, as amended).
 3. In Zone A riverine areas, in which the regulatory floodway is determined to be the channel of the river or other water course and the adjacent land areas to a distance of one-half the width of the floodplain as measured from the normal high water mark to the upland limit of the floodplain, encroachments, including fill, new construction, substantial improvement, and other development shall not be permitted unless a technical evaluation certified by a registered professional engineer is provided meeting the requirements of Section VI, paragraph I.2.
- J. New construction or substantial improvement of any structure in Zones AI-30, AE, AO AH, and A that meets the development standards of Section VI, including the elevation requirements of Section VI, paragraphs F, G, or H and is elevated on posts, columns,

piers, piles, "stilts" or crawlspaces less than three feet in height may be enclosed below the elevation requirements provided all the following criteria are met or exceeded:

1. Walls, with the exception of crawlspaces less than three feet in height, shall not be part of the structural support of the building; and,
2. Enclosed areas are not "basements"¹¹ as defined in Section XIII; and,
3. Enclosed areas shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwater. Designs for meeting this requirement must either:
 - a. be certified by a registered professional engineer or architect; or,
 - b. meet or exceed the following minimum criteria:
 - (1) a minimum of two openings having a total net area of not less than one square inch for every square foot of the enclosed area;
 - (2) the bottom of all openings shall be no higher than one foot above the lowest grade; and,
 - (3) openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the entry and exit of flood waters automatically without any external influence or control such as human intervention, including the use of electrical and other non automatic mechanical means; and,
4. The enclosed area shall not be used for human habitation; and,
5. The enclosed area may be used for building maintenance, access, parking vehicles, or storing of sections and equipment used for maintenance of the building.

K. Coastal Floodplains

1. All new construction located within Zones V1-3O or VE shall be located landward of the reach of the highest annual spring tide.
2. New construction or substantial improvement of any structure located within Zones VI-3O or VE shall:
 - a. be prohibited unless the following criteria are met:
 - (1) the area is zoned for general development or its equivalent, as defined in the Mandatory Shoreland Zoning guidelines adopted pursuant to 38 M.R.S.A. §438-A; or,
 - (2) the area is designated as densely developed as defined in 38 M.R.S.A. §436-A, subsection 3.
 - b. be elevated on posts or columns such that:
 - (1) the bottom of the lowest structural member of the lowest floor (excluding the pilings or columns) is elevated to one foot above the base flood level;
 - (2) the pile or column foundation and the elevated portion of the structure attached thereto is anchored to resist flotation, collapse, and lateral movement due to the effects of wind and water loads acting simultaneously on all building components; and,
 - (3) water loading values used shall be those associated with the base

flood. Wind loading values used shall be those required by applicable state and local building standards.

c. have the space below the lowest floor:

- (1) free of obstructions; or,
- (2) constructed with open wood lattice-work, or insect screening intended to collapse under wind and water without causing collapse, displacement, or other structural damage to the elevated portion of the building or supporting piles or columns; or,
- (3) constructed with non-supporting breakaway walls which have a design safe loading resistance of not less than 10 or more than 20 pounds per square foot.

3. A registered professional engineer or architect shall:

- a. develop or review the structural design, specifications, and plans for the construction, which must meet or exceed the technical criteria contained in the Coastal Construction Manual, (FEMA-55/February, 1986) and,
- b. certify that the design *and* methods of construction to be used are in accordance with accepted standards of practice for meeting the criteria of Section VI.K.2.

4. The use of fill for structural support in Zones VI-30 and VE is prohibited.

5. Human alteration of sand dunes within Zones VI-30 and VE is prohibited unless it can be demonstrated that such alterations will not increase potential flood damage.

6. The enclosed areas may be used solely for parking vehicles, building access, and storage.

SECTION VII-CERTIFICATE OF COMPLIANCE

No land in a special flood hazard area shall be occupied or used and no structure which is constructed or substantially improved shall be occupied until a Certificate of Compliance is issued by the Code Enforcement Officer subject to the following provisions:

A. The applicant shall submit an Elevation Certificate completed by:

1. a registered Maine surveyor for compliance with Section VI, paragraphs F, G, H, or K; and,
2. a registered professional engineer or architect, in the case of:
 - (a) floodproofed non-residential structures, for compliance with Section VI.G; and,
 - (b) construction of structures in the coastal floodplains for compliance with Section VI, paragraph K.3.

B. The application for a Certificate of Compliance shall be submitted by the applicant in writing along with a completed Elevation Certificate to the Code Enforcement Officer.

C. The Code Enforcement Officer shall review the application within 10 working days of receipt of the application and shall issue a Certificate of Compliance, provided the building conforms with provisions of this Ordinance.

SECTION VIII - REVIEW OF SUBDIVISION AND DEVELOPMENT PROPOSALS

The Planning Board shall, when reviewing subdivisions and other proposed developments that require review under other federal law, state law or local ordinances or regulations and all projects on 5 or more acres, or in the case of manufactured home parks divided two or more lots, assure that:

- A. All such proposals are consistent with the need to minimize flood damage.
- B. All public utilities and facilities, such as sewer, gas, electrical and water systems are located and constructed to minimize or eliminate flood damages.
- C. Adequate drainage is provided so as to reduce exposure to flood hazards.
- D. All proposals include base flood elevation and, in a riverine floodplain, floodway data.
- E. Any proposed development plan shall include a statement that the developer will require that structures on lots in the development be constructed in accordance with Section VI of this ordinance and that such requirement will be included in any deed, lease, purchase and sale agreement, or document transferring or expressing an intent to transfer any interest in real estate or structure, including but not limited to a time-share interest. The statement shall clearly articulate that the municipality may enforce any violation of the construction requirement and that fact shall also be included in the deed or any other document previously described. The construction requirement shall also be clearly stated on any map, plat, or plan to be signed by the Planning Board or local reviewing authority as part of the approval process.

SECTION IX- APPEALS AND VARIANCES

The Board of Appeals of the Town of Long Island may, upon written application of an aggrieved party, hear and decide appeals from administration of the provisions of this Ordinance. The Board of Appeals may grant a variance from the requirements of this Ordinance consistent with state law and the following criteria:

- A. Variances shall not be granted within designated regulatory floodway if any increase in flood levels during the base flood discharge would result.
- B. Variances shall be granted only upon:
 - 1. a showing of good and sufficient cause; and,
 - 2. a determination that should a flood comparable to the result in increased flood heights, additional threats to public safety, public expense, or create nuisances, cause fraud or victimization of the public or conflict with existing local laws or ordinances; and,
 - 3. a showing that the existence of the variance will not cause a conflict with other state, federal or local laws or ordinances; and,
 - 4. a determination that failure to grant the variance would result in “undue hardship,” which in this sub-section means:
 - a. that the land in question cannot yield a reasonable return unless a variance is granted; and,
 - b. that the need for a variance is due to the unique circumstances of the property and not to the general conditions in the neighborhood; and,

- c. that the granting of a variance will not alter the essential character of the locality, and,
 - d. that the hardship is not the result of action taken by the applicant or a prior owner.
- C. Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.
- D. Variances may be issued by a community for new construction, substantial improvements, or other development for the conduct of a functionally dependent use provided that:
 - 1. other criteria of Section IX and Section VI-I are met; and,
 - 2. the structure or other development is protected by methods that minimize flood damage during the base flood and create no additional threats to public safety.
- E. Variances may be issued by a community for the reconstruction, rehabilitation, or restoration of structures listed on the National Register of Historic Places or a State Inventory of Historic Places, without regard to the procedures set forth in Section IX, paragraphs A through D.
- F. Any applicant who meets the criteria of Section IX, paragraphs A through E shall be notified by the Board of Appeals in writing over the signature of the Chairman of the Board of Appeals that:
 - 1. The issuance of a variance to construct a structure below the base flood level will result in greatly increased premium rates for flood insurance up to amounts as high as \$25 per \$100 of insurance coverage;
 - 2. such construction below the base flood level increases risks to life and property; and,
 - 3. the applicant agrees in writing that the applicant is fully aware of all the risks inherent in the use of land subject to flooding, assumes those risks and agrees to indemnify and defend the municipality against any claims filed against it that are related to the applicant's decision to use land located in a floodplain and that the applicant individually releases the municipality from any claims the applicant may have against the municipality that are related to the use of land located in a floodplain.
- G. The Board of Appeals shall submit to the Code Enforcement Officer a report of all variance actions, including justification for the granting of the variance and an authorization for the Code Enforcement Officer to issue a Flood Hazard Development Permit, which includes any conditions to be attached to said permit.

SECTION X- ENFORCEMENT AND PENALTIES

- A. It shall be the duty of the Code Enforcement Officer to enforce the provisions of this Ordinance pursuant to 30A MRSA § 4452.
- B. The penalties contained in 30A MRSA § 4452 shall apply to any violation of this ordinance.
- C. In addition to any other actions, the Code Enforcement Officer, upon determination that a violation exists, shall submit a declaration to the Administrator of the Federal Insurance Administration requesting a denial of flood insurance. The valid declaration shall consist of:

1. the name of the property owner and address or legal description of the property sufficient to confirm its identity or location;
2. a clear and unequivocal declaration that the property is in violation of a cited state or local law, regulation or ordinance;
3. a clear statement that the public body making the declaration has authority to do so and a citation to that authority;
4. evidence that the property owner has been provided notice of the violation and the prospective denial of insurance; and,
5. a clear statement that the declaration is being submitted pursuant to Section 1316 of the National Flood Insurance Act of 1966, as amended.

SECTION XI- VALIDITY AND SEVERABILITY

If any section or provision of this Ordinance is declared by the courts to be invalid, such decision shall not invalidate any other section or provision or provision of this Ordinance.

SECTION XII-CONFLICT WITH OTHER STANDARDS

These standards shall not in any way impair or remove the necessity of compliance with any other applicable rule, ordinance, regulation, bylaw, permit, or provision of law. Where this Ordinance imposes a greater restriction upon the use of land, buildings, or structures, the provisions of this Ordinance shall control.

Any lot or portion of a lot located in a shoreland zone as identified on the town shoreland zoning map or in a flood hazard zone shall be subject to the requirements of division 26 and/or division 26.5.

SECTION XIII - DEFINITIONS

Unless specifically defined below, words and phrases used in this Ordinance shall have the same meaning as they have at common law and to give this Ordinance its most reasonable application. Words used in the present tense include the future, the singular number includes the plural, and the plural number includes the singular. The word “may” is permissive: “shall” is mandatory and not discretionary.

Adjacent Grade - means the natural elevation of the ground surface prior to construction next to the proposed walls of a structure.

Area of a Shallow Flooding- means a designated AO and All zone on a community’s Flood Insurance Rate Map (FIRM) with a one percent or greater annual chance of flooding to an average depth of one to three feet where a clean define where the path of flooding is unpredictable, and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow.

Area of Special Flood Hazard- means the land in the floodplain having a one percent or greater chance of flooding in any given year, as specifically identified in the Flood Insurance Study cited in Section I of this Ordinance.

Base Flood - means the flood having a one percent chance of being equaled or exceeded in any given year, commonly called the 100-year flood.

Basement- means any area of the building having its floor subgrade (below ground level) on all sides.

Breakaway Wall - means a wall that is not part of the structural support of the building and is intended through its design and construction to collapse under specific lateral loading forces, without causing damage to the elevated portion of the building or supporting foundation system.

Building- See Structure.

Certificate of Compliance- A document signed by the Code Enforcement Officer stating that a structure is in compliance with all of the provisions of this Ordinance.

Code Enforcement Officer - any person or board responsible for performing the inspection, licensing, and enforcement duties required by a particular statute or ordinance.

Development- means any change caused by individuals or entities to improved or unimproved real estate, including but not limited to the construction of buildings or other structures; the construction of additions or substantial improvements to buildings or other structures; mining, dredging, filling, grading, paving, excavation, drilling operations or storage of equipment or materials; and the storage, deposition, or extraction of materials, public or private sewage disposal systems or water supply facilities.

Elevated Building- means a non-basement building

- (i) built, in the case of a building in Zones A1-30, AE, A, A99, AO, or AH, to have the top of the elevated floor, elevated above the ground level by means of pilings, columns, post, piers, or “stilts;” and,
- (ii) adequately anchored so as not to impair the structural integrity of the building during a flood of up to one foot above the magnitude of the base flood.

In the case of Zones A1-30, AE, A, A99, AO, or AH, **Elevated Building** also includes a building elevated by means of fill or solid foundation perimeter walls less than three feet in height with openings sufficient to facilitate the unimpeded movement of flood waters.

Elevation Certificate - An official form (FEMA Form 81-31, 05/90, as amended) that

- (i) is used to verify compliance with the floodplain management regulations of the National Flood Insurance Program; and,
- (ii) is required for purchasing flood insurance.

Flood or Flooding - means:

- (a) A general and temporary condition of partial or complete inundation of normally dry land areas from:
 - (1) The overflow of inland or tidal waters.
 - (2) The unusual and rapid accumulation or runoff of surface waters from any source.
- (b) The collapse or subsidence of land along the shore of a lake as a result of erosion or undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually high water level in a natural body of water, accompanied by a severe storm or as flash flood or an abnormal tidal surge, or by some similarly unusual and unforeseeable event which results in flooding as defined in paragraph (a) (1) of this definition.

Flood Elevation Study- means an examination, evaluation and determination of flood hazards and, if appropriate, corresponding water surface elevations.

Flood Insurance Rate Map (FIRM)- means an official map of a community, on which the Administrator of the Federal Insurance Administration has delineated both the special hazard areas and the risk premium zones applicable to the community.

Flood Insurance Study- see Flood Elevation Study.

Floodplain or Flood-prone Area- means any land area susceptible to being inundated by water from any source (see flooding) Floodplain Management - means the operation of an overall program of corrective and preventive measures for reducing flood damage, including but not limited to emergency preparedness plans, flood control works and floodplain management regulations.

Floodplain Management Regulations - means zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances (such as a floodplain Ordinance, grading ordinance, and erosion control ordinance) and other applications of police power. The term describes such state or local regulations, in any combination thereof, which provide standards for the purpose of flood damage prevention and reduction.

Floodproofing - means any combination of structural and non-structural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities structures and contents.

Floodway- see Regulatory Floodway.

Floodway Encroachment Lines - mean the lines marking the limits of floodways on federal, state, and local floodplain maps.

Freeboard- means a factor of safety usually expressed in feet above a flood level for purposes of floodplain management. Freeboard tends to compensate for the many unknown factors, such as wave action, bridge openings, and the hydrological effect of urbanization of the watershed, that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions.

Functionally Dependent Use- means a use which cannot perform its intended purpose unless it is located or carried out in close proximity to water. The term includes only docking facilities, of cargo or passengers, and ship building and ship repair facilities, but does not include long-term storage or related manufacturing facilities.

Historic Structure- means any structure that is:

- a. Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior meeting the requirements for individual listing on the National Register;
- b. Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary of the Interior to qualify as a registered historic district;
- c. Individually listed on a state inventory of historic places in states with historic preservation programs which have been approved by the Secretary of the Interior; or

- d. Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either:
- 1) By an approved state program as determined by the Secretary of the Interior, or
 - 2) Directly by the Secretary of the Interior in states without approved programs.

Locally Established Datum- means, for purposes of this ordinance, an elevation established for a specific site to which all other elevations at the site are referenced. This elevation is generally not referenced to the National Geodetic Vertical Datum (NGVD) or any other established datum and is used in areas where Mean Sea Level data is too far from a specific site to be practically used.

Lowest Floor- means the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, usable solely for parking of vehicles, building access or storage in an area other than a basement area is not considered a building's lowest floor, provided that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements described in Section VI of this ordinance.

Manufactured Home- means a structure, transportable in one or more sections, which is built on a permanent chassis and is designed for use with or without a permanent foundation when connected to the required utilities. For floodplain management purposes the term manufactured home also includes park trailers, travel trailers, and other similar vehicles placed on a site for greater than 180 consecutive days.

Manufactured Home Park or Subdivision- means a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.

Mean Sea Level- means, for purposes of the National Flood Insurance Program, the National Geodetic Vertical Datum (NGVD) of 1929, or other datum, to which base flood elevations shown on a community's Flood Insurance Rate map are referenced.

New Construction- means structures for which the "start of construction" commenced on or after the effective date of floodplain management regulations adopted by a community and includes any subsequent improvements to such structures.

100-year flood- see Base Flood.

Regulatory Floodway-

- (i) means the channel of a river or other water course and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one foot, and
- (ii) in riverine areas is considered to be the channel of a river or other water course and the adjacent land areas to a distance of one-half the width of the floodplain, as measured from the normal high water mark to the upland limit of the floodplain.

Riverine- means relating to, formed by, or resembling a river (including tributaries) stream, brook, etc.

Special Flood Hazard Area - see Area of Special Flood Hazard.

Start of Construction- means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, substantial improvement or

other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling, nor does it include the installation of streets and/or walkways; nor does it include excavation for basement, footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

Structure- means, for floodplain management purposes, a walled and roofed building. A gas or liquid storage tank that is principally above ground is also a structure.

Substantial Damage- means, damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damage condition would equal or exceed 50 percent of the market value of the structure before the damage occurred.

Substantial Improvement- means any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market improvement. This term includes structures which have incurred substantial damage, regardless of the actual repair work performed. The term does not, however, include either:

- (1) Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions or
- (2) Any alteration of a historic structure, provided that the alteration will not preclude the structure's continued designation as a historic structure.

Variance- means a grant of relief by a community from the terms of a floodplain management regulation.

Violation- means the failure of a structure or development to comply with a community's floodplain management regulations.

SECTION XIV - ABROGATION

This ordinance repeals and replaces any municipal ordinance previously enacted to comply with the National Flood Insurance Act of 1968 (P.L. 90-488, as amended).

60.3 (e)